

## TECHNICAL DATA SHEET

**HYDROCOAT 3963**

- Type of polymer** : Aqueous pure acrylic copolymer dispersion
- Applications** :
  - Architectural interior and exterior paint.
  - Wood coating
- Feature** :
  - Excellent water & alkaline resistance
  - Excellent wet scrub resistance
  - Good color strength
  - Good film clarity and glossy
  - Good weatherability
- Packaging** : 200 kg/drum at open head iron drum with 2 liner of PE plastic bag

**Physical properties**

	<b><u>Specification</u></b>	<b><u>Unit</u></b>
▪ Solid content (150 °C / 15 min / 1 gr)	48 ± 1	%
▪ Viscosity (Brookfield LVT 4 / 60 rpm / 30 °C )	500 – 1.000	cPs
▪ pH (30 °C)	7 - 9	-
▪ Appearance	Milky white slightly transparence	-

**SHELF LIFE AND STORAGE CONDITION**

Product should be kept in the original packaging and kept closed to prevent evaporation of the water and the formation of a skin on the surface. Product should not be exposed to frost or to temperatures exceeding 40 °C. It can be kept for 8 months but it cannot be guaranteed for longer.

**PT TIRTA BINTANG FORTUNA**

Jl. Utama Modern Industri Blok AA No.3, Kawasan Industri Modern Cikande, Serang, Banten  
Indonesia . Phone: +62 254 7950011 Fax: +62 254 7950033

The information contained in this leaflet is based on our own experience. We strongly recommended tests and adaptations to varying working conditions and materials. Our technical service may be consulted. Please understand that we cannot accept any liability with regard to this information.